



822 Huber Road
Macon, GA 31217

Phone: 478 750 - 5410
Fax: 478 745 - 1116

www.kaminllc.com

Nylok[®] 171 Treated Kaolin Clay

PRODUCT DESCRIPTION

Application: Nylok 171 is an amino-functional calcined clay to speed dispersion and increase crosslink density in polyamide resin systems.

Physical Form – Fine White Powder

Type – Amino-functional anhydrous aluminum silicate

TYPICAL PHYSICAL PROPERTIES

Brightness, % Reflectance (TAPPI).....	91
% Moisture, 105°C (max), as produced,	0.5
Screen Residue, 325 mesh, max., %	0.01
pH, Post-treatment; Pre-treatment (28%).....	8.5; 6
Color.....	White
Average Stokes Equivalent Particle Diameter, microns.....	1.40
Specific Gravity.....	2.63
Crystalline Silica (quartz), %.....	<0.10
Shipping Point.....	Macon, GA

The above data are representative data for this product and should not be perceived as specifications or maximum/minimum values.

The information contained herein is believed to be accurate and reliable, but KaMin MAKES NO WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. The information herein relates only to the specific product described and not to such product in combination with any other product. Providing information as herein contained is not to be regarded by implication or otherwise as conveying any rights or permission for use which would violate any patent rights or violate any law, safety code or insurance regulation. Natural mineral products are subject to the normal variations related to the deposits from which they are mined.

©2008 KaMin LLC. KaMin and the KaMin logo are registered trademarks of KaMin LLC.

Rev. August 1, 2008