

## **Kamintex**

*Kaolin Clay - Calcined*

### **Product Description:**

Kamintex® is a high brightness calcined clay for filler and paper coating applications.

**Physical Form:** Dry

**Type:** Kaolin Clay - Calcined

### **Typical Physical Properties**

<b>Test</b>	<b>Value</b>	<b>Method</b>
Brightness, % Reflectance (TAPPI)	92 - 93.5	ASTM E1164
Moisture, 105°C, max, as produced, %	0.5	KAM-QA-WI-008
Screen Residue, 325 Mesh, %	0.005	KAM-QA-WI-001
pH, (100 g/250 ml H <sub>2</sub> O)	6-7.5	KAM-QA-WI-010

**CAS #** 1332-58-7

The above data are representative data for this product and should not be perceived as specifications or maximum/minimum values.

The information contained herein is believed to be accurate and reliable, but KaMin LLC MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. The information herein relates only to the specific product described and not to such product in combination with any other product. Providing information as herein contained is not to be regarded by implication or otherwise as conveying any rights or permission for use which would violate any patent rights, proprietary rights or violate any law, safety code or insurance regulation. Natural mineral products are subject to the normal variations related to the deposits from which they are mined.